



# G3 Regular Grade

Paste Compound



### Product Description

G3 Regular Grade Paste Compound is recommended for use on OEM and refinish paint systems.

This versatile product can be used by hand or machine. Use with a G Mop 6" Wet Use Compounding Foam (**GMC606**) for ease of use and low splatter.



### Product Information

Size	Code	Ctn Qty
250g	<b>G3-250</b>	24
400g	<b>G3-400</b>	12
1kg	<b>G3-1000</b>	12
3kg	<b>G3-3000</b>	4

### Key Benefits

• Reliable Cut	Removes P1500 or finer abrasive marks quickly and easily
• Permanent Finish	Contains no fillers so scratch marks will not reappear
• High Gloss System	Excellent gloss. Can be used with G3 Fine Finishing Compound for an enhanced gloss finish on dark colours
• Silicone Free	100% paintshop safe



## Use With

### Machine Application




G Mop 6" Wet Use  
Compounding Foam  
**GMC606**



G Mop Back Plate with  
White Interface for 6" Pads  
**BPI601** (14mm thread)  
**BPI606** (16mm thread)  
**BPI612** (5/8" thread)



Water Spray Bottle  
**WSB**




Farécla Finishing Cloth  
**FC-3** (3 x cloths)

## How To Use


### Machine Application




1 Soak a G Mop 6"  
Wet Use Com-  
pounding Foam




2 Attach pad to the  
polishing machine,  
spin off excess  
water and knead



3 Knead tube or mix  
compound well,  
then apply to pad  
or surface



4 Spread and  
compound at  
1500 - 1800rpm.  
Apply more water  
if necessary




5 Wipe clean with  
Finishing Cloth


### Hand Application



1 Soak and rinse out  
a Finishing Cloth



2 Knead tube or mix  
compound well,  
then apply to cloth  
or surface



3 Rub product on  
the surface in a  
back and forth  
motion



4 Apply water if  
necessary. Wipe  
clean with Finishing  
Cloth

## Technical Information

Appearance: **White coloured paste**

Viscosity: **Highly viscous**

VOC Content: **177g/L**

Relative Density: **1.44**

pH: **9 - 10**

Paint Type Compliance: **MS & HS**



# G6 Paste

Rapid Grade Paste Compound

## Product Description

G6 Rapid Grade Paste Compound is for use on OEM, Refinish Medium Solids and Air Dried 2k paint systems (well cured).

## Technical Information

Appearance: Cream coloured paste  
 Viscosity: High viscosity  
 VOC Content: 11.2% of total product  
 Relative Density: 1.44  
 pH: 9.41  
 Paint Type Compliance: MS & HS

## Product Information

Size	Code	Ctn Qty
400g	G6-400	12
3kg	G6-3000	4

## Key Benefits

- |                     |  |
|---------------------|--|
| • Permanent Finish  | Removes P1500 abrasive marks quickly and easily with no fillers      |
| • Silicone Free     | Can be used in bodyshops and applied nearby to where paints are used |
| • High Gloss System | Can be used with G10 Finishing Compound for an enhanced gloss finish |

## Use With


### Machine Application




G Mop 6" Standard  
Compounding Head  
**SGM-14** (Head -  
14mm thread)  
**SGM-58** (Head -  
5/8" thread)



Water Spray  
Bottle  
**WSB**



Farécla Finishing  
Cloth  
**FC-3**




Farécla Finishing  
Cloth  
**FC-3**

## How To Use


### Machine Application




Soak  
compounding  
head  
**SGM-14** (head)




Attach pad to the  
polishing machine,  
spin off excess  
water and knead



Shake bottle or mix  
compound well  
and apply to pad  
or surface  
**G6-3000** (3kg)



Spread and  
compound at  
1500 - 1800rpm




Wipe clean with  
Finishing Cloth  
**FC-3** (cloth)


### Hand Application




Soak and rinse out  
Farécla Finishing  
Cloth  
**FC-3** (cloth)  
**WSB** (water spray  
bottle)



Shake bottle or mix  
compound well  
and apply to cloth  
or surface  
**G6-3000** (3kg)



Rub product on  
the surface in a  
back and forth  
motion



Wipe clean with  
Finishing Cloth  
**FC-3** (cloth)

\*It is always recommended to test on an inconspicuous area prior to general use